

NATIONAL DECLARATION OF PERFORMANCE

nr węże/2017

1. Unique identification code of the product-type:

- a. BIDETTA ZESTAW NATRYSKOWY
- b. AERATOR NEOPERL HC M24 4,5L/MIN (INSERT+OBUDOWA Z USZCZELKĄ)
- c. AERATOR DWUFUNKCYJNY NA PRZEGUBIE CHROM
- d. AERATOR DWUFUNKCYJNY NA PLASTYFIKOWANYM WĘŻYKU CHROM
- e. AERATOR DWUFUNKCYJNY NA ELASTYCZNYM WĘŻYKU CHROM
- f. WĄŻ DO DESZCZOWNI, 50CM, Z NAKR. STOŻKOWĄ G1/2" I HEKSAGONALNĄ G1/2"
- g. WĄŻ STAL. DO BAT. ZLEW. Z WYC. WYL., 150CM Z NAKR. STOŻKOWĄ 1/2", M15
- h. WĄŻ NYLONOWY DO BAT. ZLEW., 150CM Z NAKR. STOŻKOWĄ 1/2", M15M
- i. REDUKTOR PRZEPŁYWU WODY CHROM
- j. AERATOR START-STOP PLASTIKOWY 24 MM Z REDUKCJĄ
- k. ZESTAW BIDETTA Z PRZYŁĄCZEM KĄTOWYM I UCHWYTEM NA SŁUCHAWKĘ
- l. ZESTAW BIDETTA NERO Z PRZYŁĄCZEM KĄTOWYM I UCHWYTEM NA SŁUCHAWKĘ
- m. WĄŻ NATRYSKOWY DO BAT. 3-OTWOROWYCH, 195CM Z NAKR. STOŻKOWĄ 1/2", M15M
- n. WĄŻ NATRYSKOWY DO BAT. 3-OTWOROWYCH, 150CM Z NAKR. STOŻKOWĄ 1/2", M15M
- o. WĄŻ NATRYSKOWY DO BAT. 3-OTWOROWYCH, 150CM Z NAKRĘTKĄ 1/2", M15M
- p. WĄŻ CHROM. DO BAT. ZLEW. Z WYC. WYL. 120CM Z NAKR. STOŻKOWĄ 1/2", M15M
- q. WĄŻ DO DESZCZOWNI, 60CM, DWIE NAKRĘTKI HEKSAGONALNE G1/2", NERO
- r. WĄŻ NATRYSKOWY DO BAT. HIACYNT 3 OTW. NERO BQH N13M 1/2" M15
- s. WĄŻ NYLONOWY Z PRZEGUBEM 150CM DO BAT. LIMA BBF X72M
- t. WĄŻ NYLONOWY DO BAT. ZLEW. Z WYCIĄGANĄ WYL., 150CM, M15 / M10
- u. AERATOR BLACK (CZARNY) DO BAT. BEU B62M / BEV B62M
- v. KPL. AERATOR DO BAT. ARNIKA NERO BQA N21M, N21K
- w. WĄŻ NATRYSKOWY NERO 150 CM, PCV
- x. AERATOR PREMIUM DO BAT. WANNOWYCH, GWINT ZEW. M28
- y. AERATOR STANDARD DO BAT. WANNOWYCH, GWINT ZEW. M28
- z. AERATOR DO BAT. GWINT WEW. M22
- aa. AERATOR STANDARD
- bb. AERATOR PREMIUM DO BAT. UMYWALKOWYCH I ZLEW., GWINT ZEW. M24
- cc. AERATOR BASIC DO BAT. UMYWALKOWYCH I ZLEW., GWINT ZEW. M24
- dd. AERATOR BASIC DO BAT. WANNOWYCH, GWINT ZEW. M28
- ee. AERATOR REDUKUJĄCY PRZEPŁYW WODY DO 1,9 L/MIN, GWINT ZEW. M24
- ff. AERATOR REDUKUJĄCY PRZEPŁYW WODY DO 3,8 L/MIN, GWINT ZEW. M24
- gg. AERATOR REDUKUJĄCY PRZEPŁYW WODY DO 3 L/MIN, GWINT ZEW. M24
- hh. WĄŻ NATRYSKOWY DO BAT. 3-OTWOROWYCH, 170CM Z 2X M15M
- ii. WĄŻ NATRYSKOWY MOSIĄDZ 150 CM, Z ANTI-TWIS
- jj. WĄŻ NATRYSKOWY NERO 150 CM, Z ANTI-TWIS
- kk. BIDETTA ZESTAW NATRYSKOWY, CHROM
- ll. WĄŻ NATRYSKOWY GOLD 150 CM
- mm. ZESTAW BIDETTA CHROM Z UCHWYTEM NA SŁUCHAWKĘ
- nn. ZESTAW BIDETTA NERO Z UCHWYTEM NA SŁUCHAWKĘ
- oo. REDUKTOR PRZEPŁYWU 5 L/MIN (KRYZA) G1/2"
- pp. BIDETTA ZESTAW NATRYSKOWY Z PRZELĄCZNIKIEM FUNKCJI, CHROM
- qq. REDUKTOR PRZEPŁYWU 7 L/MIN (KRYZA) G1/2

2. Designation of the construction product type: products available under codes

- | | | | | |
|-------------|--------------|--------------|---------------|---------------|
| a. ANW_041B | k. ANW_051B | u. XDCN4PLZ0 | ee. ABA24PS1 | oo. XPC00BUZ5 |
| b. ABAZ4PS4 | l. ANW_N51B | v. XDCA7PLD0 | ff. ABAZ4PS3 | pp. ANW_041C |
| c. ANN_061K | m. XDW00VCNM | w. XNCH0PLD1 | gg. ABAZ4PPS3 | qq. XPC00BUZ7 |

d. ANN_062K	n. XDWC1VCNM	x. XDC00PCZ2	hh. XDWM3VCN1
e. ANW_062K	o. XDWJ1VCNM	y. XDC00PCZ4	ii. XDCT0VFLO
f. ANW_051V	p. XPCM1VCRM	z. XPCT2PCZ0	jj. XDCT0VLL0
g. ANW_057V	q. ANW_N51V	aa. XDC00PCZ3	kk. ANW_061B
h. ANW_257N	r. XDCH2VLNM	bb. XDC00PCZ1	ll. XDCA7VFA1
i. ANR_091K	s. XDCL8VSSM	cc. XDW00PCZ1	mm. ANW_071B
j. ABAU4PDZ	t. XDCA4VXRN	dd. XDW00PCZ2	nn. ANW_N71B

3. Intended purpose or purposes: for sanitary installations to hot and cold water intended for human consumption.

4. Producer: **Deante Sp. z o.o.**
ul. Twarda 11/13, Zgierz 95-100

5. Name and address of the registered office of the authorized representative, if any: none

6. System(s) of assessment and verification of constancy of performance: 4

7. Harmonized standard
a. Notified body: PN-EN 1112:2008
b. Notified body: PN-EN 1113:2015-06
c. Notified Body: PN-EN 246:2005

8. Declared use values

Essential characteristics	Declared performance	Harmonized standard	Remark
For product components subject to PN-EN 1112			
Application range	- minimum pressure 0,5bar - recommended pressure 1÷3 bar - maximum pressure 5 bar - maximum hot water temperature: 70°C - recommended hot water temperature: ≤42°C	PN-EN 1112:2008	
Materials	pass	PN-EN 1112:2008	Part 7
Dimensions	pass	PN-EN 1112:2008	Part 8
Tightness	pass	PN-EN 1112:2008	Part 9
Mechanical properties	pass	PN-EN 1112:2008	Part 10
Hydraulic requirements (flow class)	pass	PN-EN 1112:2008	Part 11
Acoustic properties	pass	PN-EN 1112:2008	Part 12
Cleaning	pass	PN-EN 1112:2008	Part 13
Rotary connector	pass	PN-EN 1112:2008	Part 14
For product components subject to PN-EN 1113			
Application range	- minimum pressure 0,5bar - recommended pressure 1÷3 bar - maximum pressure 5 bar		

Essential characteristics	Declared performance	Harmonized standard	Remark
	- maximum hot water temperature: 70°C - recommended hot water temperature: ≤42°C		
Materials	pass	PN-EN 1113:2015-06	Part 6
Dimensions	pass	PN-EN 1113:2015-06	Part 7
Hydraulic requirements	pass	PN-EN 1113:2015-06	Part 8
Mechanical properties and tightness	pass	PN-EN 1113:2015-06	Part 9
Rotary connector	pass	PN-EN 1113:2015-06	Part 10
For product components subject to PN-EN 246			
Application range	- minimum pressure 0,5bar - recommended pressure 1÷3 bar - maximum pressure 5 bar - maximum hot water temperature: 70°C - recommended hot water: 65°C	PN-EN 246:2005	
Marking	pass	PN-EN 246:2005	Part 4 i 5
Materials	pass	PN-EN 246:2005	Part 6
Dimensions	pass	PN-EN 246:2005	Part 7
Hydraulic requirements	pass	PN-EN 246:2005	Part 8
Mechanical properties	pass	PN-EN 246:2005	Part 9 i 10
Acoustic properties	Group I	PN-EN 246:2005	Part 11

Flow class:

a. ANW_041B – A	k. ANW_051B – Z	aa. XDC00PCZ3 - S	kk. ANW_061B - Z
b. ABAZ4PS4 - Z	l. ANW_N51B – Z	bb. XDC00PCZ1 - A	mm. ANW_071B - Z
c. ANN_061K - Z	q. XDCN4PLZ0 - Z	cc. XDW00PCZ1 - C	nn. ANW_N71B - Z
d. ANN_062K - Z	r. XDCA7PLD0 – Z	dd. XDW00PCZ2 - B	oo. XPC00BUZ5 - Z
e. ANW_062K – Z	x. XDC00PCZ2 - B	ee. ABAZ4PS1 - Z	pp. ANW_041C - Z
i. ANR_091K - 23-0 l/min	y. XDC00PCZ4 - B	ff. ABAZ4PS3 - Z	qq. XPC00BUZ7 - Z
j. ABAU4PDZ – Z	z. XPCT2PCZ0 - Z	gg. ABAZ4PPS3 - Z	

9. The performances of the product identified above are compatible with all declared performances listed in point 8. Presented national declaration of performance is issued in accordance with the Act of 16th April 2004 on construction products, on the sole responsibility of the manufacture.

Łódź, 18.04.2017

Update: I 16.04.2018, II 07.12.2020

III 05.07.2022, IV 30.12.2022, V 08.05.2023,

VI 13.05.2024, VII 01.07.2024, VIII 16.09.2024, IX 25.11.2025



Wojciech Burkowski
Chief Executive Officer
DEANTE Ltd

